

Punches CONFIX™

for CONFIX™ bulkhead fittings, for steel, aluminium, stainless steel



These punches can be used to punch the special cutout shapes for the CONFIX™ bulkhead fittings.

For max. 2 mm stainless steel (V2A versions), sheet steel, aluminium and plastic.

The punches are suitable for the hand hydraulic punch driver and the hydraulic foot pump. For the FWS-A 50 / FWS-B 48 punches, we only recommend the hydraulic foot pump.

Scope of delivery:

- Punch, die, counter nut and draw stud
- robust plastic storage case

Specifications

Material	Steel, hardened and burnished
----------	-------------------------------

Advantages & benefits

- For the special cut-out shapes for CONFIX™
- High-quality padded transport case
- Suitable for hand hydraulic punch driver by icotek or other manufacturers

Product types & sizes

Punch FWS-A16/20 / FWS-B11/16



Part No.	80095	Max. wall	2 mm
EAN	4251269333	thickness	
Package quantity	1		
Number of centre punches	3		
Compatible with CONFIX™ FWS	FWS-A 16, FWS-A 20, FWS B11, FWS-B 16		
Thread UNF	19 mm		
Punching material	Plastic, Mild steel (St)		

Punch FWS-A16/20 / FWS-B11/16 V2A



Part No.	80195	Max. wall	2 mm
EAN	4251269333	thickness	
	354		
Package quantity	1		
Number of centre punches	3		
Compatible with CONFiX™ FWS	FWS-A 16, FWS-A 20, FWS B11, FWS-B 16		
Thread UNF	19 mm		
Punching material	Stainless steel (V2A)		

Punch FWS-A 25 / FWS-B 21



Part No.	80096	Max. wall	2 mm
EAN	4251269333	thickness	
	323		
Package quantity	1		
Number of centre punches	3		
Compatible with CONFiX™ FWS	FWS-A 25, FWS-B 21		
Thread UNF	19 mm		
Punching material	Plastic, Mild steel (St)		

Punch FWS-A 25 / FWS-B 21 V2A



Part No.	80196	Max. wall	2 mm
EAN	4251269333	thickness	
	361		
Package quantity	1		
Number of centre punches	3		
Compatible with CONFiX™ FWS	FWS-A 25, FWS-B 21		
Thread UNF	19 mm		
Punching material	Stainless steel (V2A)		

Punch FWS-A 32 / FWS-B 29



Part No.	80097	Max. wall	2 mm
EAN	4251269333	thickness	
	330		
Package quantity	1		
Number of centre punches	4		
Compatible with CONFiX™ FWS	FWS-A 32, FWS-B 29		
Thread UNF	19 mm		
Punching material	Plastic, Mild steel (St)		

Punch FWS-A 32 / FWS-B 29 V2A



Part No.	80197	Max. wall	2 mm
EAN	4251269333	thickness	
	378		
Package quantity	1		
Number of centre punches	4		
Compatible with CONFiX™ FWS	FWS-A 32, FWS-B 29		
Thread UNF	19 mm		
Punching material	Stainless steel (V2A)		

Punch FWS-A 40 / FWS-B 36



Part No.	80098	Max. wall	2 mm
EAN	4251269333	thickness	
	347		
Package quantity	1		
Number of centre punches	4		
Compatible with CONFiX™ FWS	FWS-A 40, FWS-B 36		
Thread UNF	19 mm		
Punching material	Plastic, Mild steel (St)		

Punch FWS-A 40 / FWS-B 36 V2A



Part No.	80198	Max. wall	2 mm
EAN	4251269333	thickness	
	385		
Package quantity	1		
Number of centre punches	4		
Compatible with CONFiX™ FWS	FWS-A 40, FWS-B 36		
Thread UNF	19 mm		
Punching material	Stainless steel (V2A)		

Punch FWS-A 50 / FWS-B 48



Part No.	80099	Max. wall	2 mm
EAN	4251269333	thickness	
	255		
Package quantity	1		
Number of centre punches	4		
Compatible with CONFiX™ FWS	FWS-A 50, FWS-B 48		
Thread UNF	19 mm		
Punching material	Plastic, Mild steel (St)		



Part No.	80199	Max. wall	2 mm
EAN	4251269333	thickness	
	262		
Package	1		
quantity			
Number of	4		
centre			
punches			
Compatible	FWS-A 50,		
with CONFIX™	FWS-B 48		
FWS			
Thread UNF	19 mm		
Punching	Stainless		
material	steel (V2A)		