

Knockout punch set 16-63

Knockout punches, round M16 - M63



Self-centering knockout punches for stainless steel or mild steel, aluminium and plastic walls with max. sheet thickness of 3 mm. Punches for cut-outs M16, M20, M25, M32, M40, M50 and M63. Cut-outs for icotek split cable glands and round cable entry plates can be punched.

The special cutting geometry of the punch reduces the cutting pressure and therefore the required effort. The punch splits slugs into several pieces (type related) for easy slug removal.

The punches are designed for manual and hydraulic operation.

Scope of delivery:

- 1 each knockout punch M16 | M20 | M25 | M32 | M40 | M50 | M63

Specifications

Material	Steel, hardened and burnished
----------	-------------------------------

Advantages & benefits

- Multiple splitting punches for easier slug removal/ for easy punching
- Suitable for hand hydraulic punch driver by icotek and other manufacturers

Product types & sizes

Punch V2A set M16 - M63



Part **80070**

No.

EAN **42512**

69323

935

Packag

1

e

quanti

ty

Punchi

Stainl

ng

ess

materi

al

(V2A)

Suitabl

80201

e draw /

stud

80210

Part **80007**

No.

EAN **42512**

69316

579

Packag**1**

e

quanti

ty

Punchi **Plasti**

ng **C**,

materi **Mild**

al **steel**

(St)

Suitabl**80200**

e draw /

stud **80201**



icotek[®]
smart cable management