

Punches CONFiX™

for CONFiX™ bulkhead fittings, for steel, aluminium, stainless steel



These punches can be used to punch the special cutout shapes for the KEL-FW bulkhead fittings.

For max. 2 mm stainless steel (V2A versions), sheet steel, aluminium and plastic.

The punches are suitable for the hand hydraulic punch driver and the hydraulic foot pump. For the punches, we only recommend the hydraulic foot pump.

Scope of delivery:

- Punch, die, counter nut and draw stud
- robust plastic storage case

Specifications

Material	Steel, hardened and burnished
----------	-------------------------------

Advantages & Benefits

- For the special cut-out shapes for KEL-FW
- High-quality padded transport case
- Suitable for hydraulic punch drivers by icotek or other manufacturers

Product Types & Sizes

Punch KEL-FW



Part No.	80100
EAN	4251269335
	099
Package quantity	1
Number of center punches	4
Thread UNF	19 mm
Punching material	Plastic, Mild steel (St)
Max. wall thickness	2 mm



Part No.	80194
EAN	4251269335
	105
Package	1
quantity	
Number of	
center	
punches	
Thread UNF	19 mm
Punching	Stainless
material	steel (V2A)
Max. wall	
thickness	2 mm

icotek[®]
smart cable management