

Punches CONFIX™

for CONFIX™ bulkhead fittings, for steel, aluminium, stainless steel



WE
CONTROL
COMPONENTS

Bestel direct online @ CC Nederland »



Voor aanvragen uit België [klik hier](#) »

These punches can be used to punch the special cutout shapes for the KEL-FW bulkhead fittings.

For max. 2 mm stainless steel (V2A versions), sheet steel, aluminium and plastic.

The punches are suitable for the hand hydraulic punch driver and the hydraulic foot pump. For the punches, we only recommend the hydraulic foot pump.

Scope of delivery:

- Punch, die, counter nut and draw stud
- robust plastic storage case

Specificaties

Materiaal	Staal, gehard en gepolijst
------------------	----------------------------

Voordelen

- For the special cut-out shapes for KEL-FW
- High-quality padded transport case
- Suitable for hydraulic punch drivers by icotek or other manufacturers

Producttypes en maten

Punch KEL-FW



Art.nr.	80100
EAN	4251269335099
Aantal	1
Aantal	4
centerponspunten	
Schroefdraad	19 mm
UNF	
Ponsbaar materiaal	Kunststof, staal (St)
Max. wanddikte	2 mm



Art.nr.	80194
EAN	4251269335
	105
Aantal	1
Aantal	4
centerponspunten	
Schroefdraad	19 mm
UNF	
Ponsbaar materiaal	Roestvrij staal V2A
Max. wanddikte	2 mm