

Punches CONFIX™

for CONFIX™ bulkhead fittings, for steel, aluminium, stainless steel



These punches can be used to punch the special cutout shapes for the KEL-FW bulkhead fittings.

For max. 2 mm stainless steel (V2A versions), sheet steel, aluminium and plastic.

The punches are suitable for the hand hydraulic punch driver and the hydraulic foot pump. For the punches, we only recommend the hydraulic foot pump.

Scope of delivery:

- Punch, die, counter nut and draw stud
- robust plastic storage case

Specifikationer

Material	Stål, härdat och förbränt
----------	---------------------------

Fördelar

- For the special cut-out shapes for KEL-FW
- High-quality padded transport case
- Suitable for hydraulic punch drivers by icotek or other manufacturers

Produkttyper och storlekar

Punch KEL-FW		
	ArtNr.	80100
	EAN	4251269335099
	Antal	1
	Number of centre punches	4
	Tråd UNF	19 mm
	Stansbart material	Plast, stål (St)
	Max. väggjocklek	2 mm

Punch KEL-FW V2A

ArtNr.	80194
EAN	4251269335
	105
Antal	1
Number of centre punches	4
Tråd UNF	19 mm
Stansbart material	Rostfritt stål V2A
Max. vägg tjocklek	2 mm



icotek[®]
smart cable management